Panasonic

350/500GL3

The World's Most Preferred and Reliable Fully Digital Pulse MIG/MAG Welding Machine



High quality welding for Stainless Steel and Mild Steel

World-class welding quality at your doorstep



Panasonic Welding Systems India has set-up its state-of-the-art manufacturing facility in India. So our globally proven range of welding equipment including MMAW, MIG/MAG, TIG, Plasma Cutting, Welding Accessories, and Welding Robots are now available at your doorstep.

With a nationwide network of dealers and prompt service and support, you can be sure of quality and performance that are truly world-class.

Key features of 350/500GL3

- Makes high quality and high power pulse welding easier
- GL Pulse Control- Independently developed by Panasonic

Pulse Control Method

Hybrid Pulse Control
Soft Pulse Control
Hard Pulse Control





 Full Digital Control- allows precision and high welding performance

- Practical welding management function
 - As many as nine sets of optimal parameters can be stored and recalled instantly
 - The pre-set parameters are can be locked as read-only data

High performance wire feeding device

■ Wire Feed Motor with Encoder- allows precision wire feed





- The motor attached with encoder ensures accurate feeding of welding wire, realising uniformed welding bead
- The stable feeding is obtainable even when external factors such as power supply, voltage, and wire feeding change
- Stable wire feeding-same welding condition is repeatable at various surroundings
- 2 drive, 2-slave feeding method adopts 2-point feeding with strong feeding force. The stable feeding is realised when stainless-steel welding wire, flux-cored welding wire and the torch with extension cable is used
- Faster service support across India
- All Panasonic Welding Equipment arc RoHS compliant





http://panasonic.net/pws

 \oplus

Authorised Sales & Service Provider

Technical Specifications

Technical Specification	Unit	350GL3	500GL3
Rated Input Voltage	V	415 VAC (Allowable fluctuation range: -10% to +10%)	415 VAC (Allowable fluctuation range: -10% to +10%)
Rated Frequency	Hz	50/60Hz (Common)	50/60Hz (Common)
Number of Phase		3-phase	3-phase
Rated Input	kVA	14.5	23.3
	kW	14	22.4
Maximum Non-load Voltage	V	72 DC	68 DC
Rated Output Current	Α	350 DC	500 DC
Rated Output Voltage	V	31.5 DC	45 DC
Output Current Adjustable Range	Α	30 -430	60 -500
Output Voltage Adjustable Range	V	16 -35.5	17 -45
Rated Duty Cycle	%	60	100
Power Control Method	-	IGBT inverter type	IGBT inverter type
Memory	-	9 ch, reproducible storages	9 ch, reproducible storages
Applicable Welding Method	-	CO2, MAG, Stainless steel MIG	CO2, MAG, Stainless steel MIG
Waveform Control Method	-	Digital control: -7 (small) to +7 (large) (Standard: 0)	Digital control: -7 (small) to +7 (large) (Standard: 0)
Sequence	-	Main welding, Main welding - Crater ("Crater repeat" is available), Initial - Main welding - Crater ("Crater repeat" is avaiable), Arc spot	Main welding, Main welding - Crater ("Crater repeat" is available), Initial - Main welding - Crater ("Crater repeat" is avaiable), Arc spot
Applicable Shielding Gas		CO2 (100%), MAG (80% argon and 20% CO2) Stainless steel MIG (98 % argon and 2 % oxygen)	CO2 (100%), MAG (80% argon and 20% CO2) Stainless steel MIG (98 % argon and 2 % oxygen)
Applicable Wire Size (Diameter)		0.8,0.9, 1.0, 1.2	1.2, 1.4, 1.6
Applicable Wire Material (Note)		Mild steel (MS) Flux cored mild steel (MS_FCW) Stainless steel Flux cored stainless steel (SUS-FCW)	Mild steel (MS) Flux cored mild steel (MS_FCW) Stainless steel Flux cored stainless steel (SUS-FCW)
Gas Purge Time	-	1 second - 1 minute / continuous	1 second - 1 minute / continuous
Pre-flow Time	S	0.0 - 5.00 (Increment of 0.1) continuous	0.0 - 5.00 (Increment of 0.1) continuous
Post-flow Time	S	0.0 - 5.00 (Increment of 0.1) continuous	0.0 - 5.00 (Increment of 0.1) continuous
Arc Spot Time	-	0.3 - 10.0 (Increment of 0.1) continuous	0.3 - 10.0 (Increment of 0.1) continuous
Input PowerTerminal	-	Terminal block (for 3-phase, M5 bolting)	Terminal block (for 3-phase, M5 bolting)
Output Terminal	-	Copper terminal with M8 bolting	Copper terminal with M8 bolting
Dimension (Width x Depth x Height)	mm	380X 550X645	380X 550X815
Mass	kg	50	60
Ordering Information			
Power Source	-	YD-350GL3HJE	YD-500GL3HJE
Wire Feeder	-	YW-35DG1HA1	YW-50DG1HA1
Torch	-	YT-35CS4HAF/ YT-35CS4DAF	YT-50CS4HAF/ YT-50CS4DAF

Panasonic

Range of Welding Equipment: MMAW | MIG/MAG | TIG | Plasma Cutting | Welding Accessories | Welding Robots

For more information please write to welding.info@in.panasonic.com. For service related queries, write to welding.service@in.panasonic.com

Panasonic India Pvt. Ltd.

(Division Company: Panasonic Welding systems India) Factory, Head Office and Northern Regional Office

Village Bid Dadri, Tehsil and District: Jhajjar- 124103, Haryana, India

Tel.: +91-124-6676372 / 73, Fax: +91-124-6676338 Email: welding.north@in.panasonic.com

Eastern Regional Office: No 1, Vikash Towers, Dr. UN Brahmachari Street, 3rd Floor, Opp. ITC Fortune Hotel, Kolkata 700 016, West Bengal. Phone: +91-33-40269696.

Email: welding.east@in.panasonic.com
Western Regional Office: Technical Centre, Panasonic Welding Systems India, MCCIA-Navalmal Firodia Excellence Centre, J-462, M.I.D.C., Telco Road, Bhosari, Pune 411026, Maharashtra.

Phone: 09890284448. Email: welding.west@in.panasonic.com
Southern Regional Office: 6th Floor, SPIC Building Annexe, No. 88, Mount Road, Guindy, Chennai 600032, Tamilnadu. Phone: +91-44-61089300. Fax: +91-44-61089399.

Email: welding.south@in.panasonic.com Central Regional Office: Ayodhya, 119, 2nd Floor, Bajaj Nagar, Nagpur 440010, Maharashtra. Email: welding.central@in.panasonic.com

Japan Factory: 1-1, 3-chome, Inazu-cho, Toyonaka, Osaka 561 0854, Japan China Factory: No. 9 Qingnan Rd, Tangshan New & Hi-tech Industrial Park, Hebei, China Sales Offices at Ahmedabad, Bengaluru, Bhubaneswar and Mumbai.

http://panasonic.net/pws



